

**MILCHMOBIL – MAKES
MILK MOBILE.**



**MILCHMOBIL+:
NEW DESIGN WITH
DRIVE UNIT**



THE WAY TO MOVE YOUR RESERVES.



Supplying feed to calves in individual pens or igloos used to require a lot of time and effort. The new MilchMobil+ and the tried and trusted MilchMobil from Förster-Technik make it easier for you to mix, warm, transport and dispense the feed. This saves a considerable amount of time.

The MilchMobil from Förster-Technik are distinguished by their solid stainless steel chassis and large, air-filled tires. The horizontal stainless steel tank allows for easy access for straightforward cleaning. The drain tap allows for easy filling of the feed bucket and full draining of detergent residues.

Proven reliable design

The MilchMobil has proven itself reliable over many years of use under real conditions and is available in four models with volumes of 100 and 180 liters: Tank trolley to transport the milk, mixer trolley to prepare milk substitute feed, heating trolley to warm the milk, combined trolley with mixer and heater. The new model, MilchMobil+, expands the product range to include a combined version with a capacity of 200 liters.

Standard equipment

Each model is equipped with an easily readable fill-level indicator in liters. This facilitates feed preparation, especially when using milk powders. The series also comes equipped with a temperature indicator.

Heater

The heater ensures the correct output temperature of the milk thanks to a warm water bath installed underneath the milk tank. This means the freshly-milked milk is gently kept at the desired temperature without burning on the bottom.



A timer allows for pre-heating for up to 3 feeding times.

Mixer

In the mixer and combined trolley, the powerful mixer with a large beater ensures that the milk is mixed homogeneously and without clumps.



In the MilchMobil+ an interval switch on the mixer also functions as a stirrer, which prevents the milk from creaming and accelerates the heating process.



MilchMobil

MilchMobil+

MILCHMOBIL+

Electronic control

The integrated control system with user interface makes mixing, preparation, feeding and cleaning even easier. For example, the mixing function calculates the ideal mixing ratio of water and milk powder. You can also use the selector key function to program any 3 feed quantities into direct shortcut keys.



MilchMobil+ with new control system

MILCHMOBIL+

Drive unit

The electrical drive unit is operable with both hands, and makes it easier for you to transport the feed on uneven ground.

MILCHMOBIL+

Tank cover

A stainless steel cover attached to the milk tank prevents milk from overflowing during transport.

MILCHMOBIL+

Pivoting arm

The height-adjustable pivoting arm facilitates distribution of the feed. This saves time, especially when you have to feed many calves.



Quick and easy dispensing

Tank lid

To keep the milk warmer for longer and protect against flies, the MilchMobil can be equipped with a plastic lid or a stainless steel tank cover.

MilchMobil options

Dosing pump

The battery-powered dosing pump makes it possible to dispense the feed quickly and easily anywhere by means of a filling pistol. The dosing pump with portion control saves you even more time while providing better accuracy. A selector switch is used to set the desired quantity of feed in liters and dispense it at the push of a button.

Technical data

Models	MilchMobil+ 200 liters	MilchMobil 180 liters	MilchMobil 100 liters
Tank trolley	-	135 x 67 x 110	95 x 67 x 115
Mixer trolley	-	135 x 67 x 128	95 x 67 x 120
Heating trolley	-	150 x 67 x 110	110 x 67 x 115
Combined trolley	120 x 70 x 110	150 x 67 x 128	110 x 67 x 120

Dimensions: Length x Width x Height in cm

Components	MilchMobil+ 200 liters	MilchMobil 180 liters	MilchMobil 100 liters
Mixer	0.37 kW / 230 V	0.37 kW / 230 V	0.37 kW / 230 V
Heater	4.5 kW / 400 V	10 kW / 400 V	3 kW / 400 V
Lead gel battery	24 V / 50 Ah (2 x 12 V / 50 Ah)	12 V / 36 Ah*	12 V / 36 Ah*
Dosing pump	-	12 V / max. 7.4 A	12 V / max. 7.4 A
Portion control	24 V / max. 8 A	12 V / max. 17 A	12 V / max. 17 A
Drive unit	24 V	-	-
Main power supply	400 V / 50 Hz	-	-

* only in combination with dosing

MilchMobil+ comes standard with control system, user interface, dosing pump, drive unit, tank cover.



Förster-Technik GmbH

Gerwigstr. 25
D-78234 Engen, Germany
Phone: +49 (0) 7733 9406-0
Fax: +49 (0) 7733 9406-99
E-mail: info@foerster-technik.de
Internet: www.foerster-technik.de

**FÖRSTER
TECHNIK®**
Automatisch besser.